



GOODFELLOW *Terra*®

Sealer for Cuts in Pressure Treated Wood

Goodfellow Terra® Sealer is a colour-matched brush-on sealer and moisture repellent for cuts and holes in pressure treated wood that expose untreated wood, making it more vulnerable to rot and decay.

- For use **above ground** on deck boards, railing, post tops and fence boards
- Colour closely matches Goodfellow Terra Treated Wood
- Water-based formulation is low VOC and low odour
- Ready to use, directly from the can
- Soap and water clean-up / no special disposal requirements



Sealed
Wood

Exposed
Wood



Uses

For use on **Above Ground** treated wood products. Use Goodfellow Terra Sealer on areas that have been drilled or saw cut in treated wood deck boards, railing, post tops, fence boards, etc.

A 946 ml can will seal approx. 330 5/4x6 deck board ends or approx. 220 2x6 deck board ends, coated twice.

Goodfellow Terra® Sealer is not recommended to replace pressure treatment.

Do not use for pressure treated wood in ground contact applications or in preserved wood foundations.

Application

- Pressure treated wood should be dry and clean.
- Goodfellow Terra Sealer is ready to use – do not dilute.
- Shake or stir contents before and during use.
- Apply two coats by brush.
- Clean equipment (brushes, etc.) with soap and water.
- Store in tightly closed original container. **Do not freeze.** Keep above 4° C (40° F).
- Dispose of empty container in household trash.