

# SILVER

*A New Generation of Underlayments*



**GRIPSPOT  
TECHNOLOGY**

## **SILVER - A New Generation of Underlayments. Protecting You and Your Roof**

Our GRIPSPOT™ TECHNOLOGY is your ultimate slip resistant protection when you're working on the roof.



FT Synthetics products come with over two decades of research through listening to our customers, engineers, architects, roofing contractors/installers and home owners. Our products provide ultimate high performance and protection for the installer and your home. Our products are fully synthetic, 100% recyclable, offer superior grip protection, excellent UV resistance, are the most pliable and of course are easy to use. They are light weight but durable and provide the best protection available in the market. **SILVER** is your cost effective and reliable 15 lb felt replacement product, which is easy to carry, and has 2.5X more coverage per roll as compared to felt.

- GRIPSPOT™ technology for superior slip resistance
- Product thickness 12 mils
- 90 day UV resistant
- Greater coverage per roll
- 100% recyclable water resistant polyolefin construction
- Wrinkle free and low temperature flexibility for ease of installation

## **GRIPSPOT™ TECHNOLOGY** (Patent Pending #61935797)

GRIPSPOT™ Technology is your ultimate protection on the roof, working in any weather condition. FT Synthetics has focused its research towards roofer safety and ease of use. FT Synthetics incorporates its patented GRIPSPOT™ technology, with its raised fibrous spots for traction and smooth channels for shedding water, to provide outstanding slip resistance. **SILVER** is light weight, easy to carry, cool to the touch and pliable under extreme temperatures. **SILVER** has a wrinkle free surface, lays flat and straight over longer distances (unlike many products in the market which ripple and curve) and stays put with its underside non slip coating. All of these features combined with its print design result in easier, faster and more accurate installations. **SILVER** can be used in most types of installations, whether they are commercial or residential. It can be used with wood, asphalt & synthetic shingles and residential metal roofing. **SILVER** meets and exceeds required industry standards.

ASTM D226-97  
ASTM D4869  
CAN/CSA A123.3




CAN/ CSA A220.1  
ASTM E108  
CCRR 1028  
AC188



Unit 1-13120 - 76th Avenue  
Surrey BC V3W 2V6  
Canada

Toll Free Ph: 1-844-353-9839  
Phone: 604-594-3439  
Fax: 604-594-3589  
[www.ftsyntax.com](http://www.ftsyntax.com)



# SILVER

*A New Generation of Underlayments*

## FT SYNTHETICS SILVER

### General Specifications

	SILVER	#15 Felt
Width inch	48	36
Weight per roll	22 lb	45 lb
Length in feet	250	144
Rolls per Pallet (44 x 44)	49	25
Rolls per Truckload - 36 Skids	1764	1000
Rolls Required per 1,000 Sq feet	1	2.5
100% recyclable	Yes	No
Material Composition	Polyolefin	Asphalt
UV Resistance	3 Months	None
Breaking Strength ASTM D 5034 MD	102 lb (46 kg)	NA
Breaking Strength ASTM D 5034 CD	96 lb (44 kg)	NA
Tear Strength ASTM D4533 MD	25 lb (11 kg)	NA
Tear Strength ASTM D4533 CD	23 lb (10 kg)	NA
Water shower Exposure ASTM D 4869	Pass	NA
Permeability ASTM E96	<0.05 Perms	5 Perms
Mullen Burst	113 psi	NA
Nominal Thickness ASTM D1777	12 mils	21 mils
Temperature Range	-40°F to 240°F	
Enhanced Slip Resistant Surface	Excellent	Basic
Limited Warranty	20 Years	None

The Data shown above is based on the test averages and independent test reports. There can be a +/-10% variation in the individual test results. This report should not be considered as a warranty for the manufacturer. The manufacturer is not responsible for the misrepresentation or misinterpretation of the Data by the reader. Please find out more about the product by calling 1-844-353-9839 or visit [www.ftsyn.com](http://www.ftsyn.com). The FT Synthetics Logo and GRIPSPOT™ are registered trademarks of FT Synthetics Inc.

ASTM D226-97  
ASTM D4869  
CAN/CSA A123.3



CAN/CSA A220.1  
ASTM E108  
CCRR 1028  
AC188



**FT SYNTHETICS**

Unit 1-13120 - 76th Avenue  
Surrey BC V3W 2V6  
Canada

Toll Free Ph: 1-844-353-9839  
Phone: 604-594-3439  
Fax: 604-594-3589  
[www.ftsyn.com](http://www.ftsyn.com)