

Material Safety Data Sheet

PRODUCT NAME: Exact Color [100% Acrylic, High Performance Elastomeric Sealant]
PRODUCT Description: 1) Tintable caulk base (7.75 fluid oz) in caulk cartridge*, 2) plus, separately packaged liquid thickening activator (12.5 ml)**

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Sashco, Inc.
ADDRESS: 10300 E. 107th Place, Brighton, Colorado 80601
PHONE: 1-303-286-7271
EMERGENCY PHONE: 1-800-535-5053
INFORMATION PHONE: 1-800-767-5656
DATE REVISED: January 4, 2013
REPLACES: 9-16-10
REASON FOR REVISION: Annual Review
CODE IDENTIFICATION: EXC
PRODUCT IDENTIFICATION: Exact Color [Tintable 100% Acrylic Latex, High Performance Sealant]

Health	HMIS Ratings		Reactivity	PPE
	Flammability			
1	0	0	B	

===== SECTION II - HAZARDOUS INGREDIENTS =====

INGREDIENT	CAS#	WT.%	TLV	PEL	VAPOR PRESSURE
For the tintable caulk base >					
Ethylene Glycol*	000107-21-1	1.0-3.5	50PPM	50PPM	0.12 mmHg @ 25C
For the thickening activator >					
Amino Methyl Propanol**	124-68-5	25-35	Not Establ	Not Establ	<1 mm Hg @ 25C

* The Threshold Limit Value (TLV) is the time weighted average (TWA) to which it is believed that most workers may be exposed 8-10 hours per day, 40 hours per week, without adverse health effects.
This chemical is subject to the reporting requirements of section 313 of SARA Title III.
**Amino Methyl Propanol is the active component of the thickening activator, along with water. This active ingredient is cleared for use in indirect contact applications related to food.

===== SECTION III - PHYSICAL DATA =====

SPECIFIC GRAVITY (H₂O=1): 1.01 – 1.06 (caulk base), 0.983 (thickening activator)
PERCENT VOLATILE BY VOLUME (%): 38-42% [Mostly water, less than 1.5% VOC by weight]
EVAPORATION RATE (WATER =1): >1
SOLUBILITY IN WATER (cured film): Negligible [Both components are water soluble otherwise]
APPEARANCE AND ODOR: Semi-fluid paste after being thickened; mild, sweet odor
BOILING POINT (F): N/A
VAPOR PRESSURE (mm Hg.): N/A
VAPOR DENSITY (AIR=1): N/A
pH of the thickening activator 12.45 – 12.75
pH of the caulk base 6.5 – 7.0
pH of combined caulk base and activator 8.6 – 9.2

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (F): N/A

FLAMMABLE LIMITS: N/A
EXTINGUISHING MEDIA: Normal procedures
SPECIAL FIRE FIGHTING PROCEDURES: Direct water spray may cause frothing.
UNUSUAL FIRE AND EXPLOSION HAZARDS: None known

===== SECTION V - HEALTH HAZARD DATA =====

THRESHOLD LIMIT VALUE: N/A
EFFECTS OF OVEREXPOSURE: None known for the liquid caulk base
EFFECTS OF OVEREXPOSURE: Skin & eye irritation/burns with thickening activator
EMERGENCY AND FIRST AID PROCEDURES:
Caulk base: If product has been ingested, administer two glasses of water and contact a physician. If material comes in contact with eyes, rinse thoroughly for at least 20 minutes. If irritation persists, contact a physician.
Thickening Activator: 1) Skin: immediately wash with large amount of water. Launder clothing wet with activator. 2) Eyes: immediately flush with large amount of water for 15 minutes. See a physician. 3) Ingestion: neutralize swallowed activator with dilute vinegar. Do not induce vomiting.

===== SECTION VI - REACTIVITY DATA =====

STABILITY: Stable
INCOMPATIBILITY: None known
HAZARDOUS DECOMPOSITION PRODUCTS: None known
HAZARDOUS POLYMERIZATION: Will not occur

===== SECTION VII - SPILL OR LEAK PROCEDURES =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Wipe or scrape up and dispose. No special precautions are required.

WASTE DISPOSAL METHOD:
Dispose in a sanitary landfill or incinerate according to local and federal regulations.

===== SECTION VIII - SPECIAL PROTECTION INFORMATION =====

RESPIRATORY PROTECTION: None needed
VENTILATION: Local exhaust, general
PROTECTIVE GLOVES: Rubber gloves recommended when handling the activator.
EYE PROTECTION: Safety glasses recommended when handling the activator.
OTHER PROTECTIVE EQUIPMENT: None required

===== SECTION IX - SPECIAL PRECAUTIONS =====

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store at room temp. Keep from freezing.
OTHER PRECAUTIONS: Keep away from children. Wash hands with soap and water after handling the colorant and thickener.
SHIPPING INFORMATION: Exact Color is not regulated under and DOT classification due to posing little or no hazard.

===== SECTION X - DISCLAIMER =====

DISCLAIMER:
The information contained herein is based on data available at the time of preparation of this data sheet and which Sashco Inc. believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. Sashco, Inc. shall not be responsible for the use of this information or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment and the health and safety of your employees and users of this material.