



Commercial grade for most severe weather



Canadian weather is tough. DRYline® HP is tougher.

Commercial-grade building wrap that stands up to the elements.

Made from strong non-woven fabrics, DRYline HP is the ideal choice for residential and commercial projects with high-perm moisture transfer

requirements. Plus, with our exclusive BROADCAST® Custom Printed Advertising, you can display any custom logo or advertising message on your DRYline wrap — which can be ordered in the industry's smallest quantities.

What Makes Dryline HP Superior?

- **DURABLE:** Stays fastened for longer, and stronger than the leading product in the category.
- **BREATHABLE:** Enables the highest level transfer of moisture vapor.
- **WEATHER-RESISTANT:** Provides water resistance while limiting air movement within the wall cavity.
- **ENERGY-EFFICIENT:** Recognized as an air barrier material for energy-efficiency standards.
- **SIMPLER:** Application is easier, with translucence for locating studs, openings, and corners quickly and easily.
- **COMPLIANT:** Meets or exceeds code requirements for water-resistant barriers and air barriers.
- **UV RESISTANT:** May be left exposed for up to 180 days — longer than competitive products.

DryLINE - Exclusively distributed in Canada by Goodfellow



For over 120 years, Goodfellow has been an industry leader in the distribution of building materials. With coast-to-coast distribution centers, they can service all regions in Canada, which enables customer's expectations to be met and exceeded time and time again in terms of quality and delivery lead times.

WARRANTY INFORMATION

A ten (10) year limited warranty applies to DRYline HP building wrap. To obtain a copy of this warranty, please visit drylinewrap.com. No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

PRECAUTIONS

Warning: Protect from high heat or other ignition sources during shipment, storage and application.

STORAGE

Protect DRYline building wrap from exposure to direct sunlight during storage. We recommend storage inside or under cover.

ROLL SIZES*

3' x 150' 9' x 100' 9' x 150' 9'6" x 95'
10' x 90' 10' x 100' 10' x 150'

Other roll sizes available

* Not all rolls available for BROADCAST Custom Printed Advertising, ask your sales representative for more details.

PROPERTY	STANDARD	TYPICAL RESULT
Tensile Strength (MD/CD)	ASTM D 5034 (lbs/inch)	65/45
Basis Weight	ASTM D 5261 (gsm)	80
Water Vapor Transmission Rate	ASTM E 96, Method A (grams/m ² /24 hours)	420
Water Vapor Permeance	ASTM E 96, Method A (perms)	60
Water Resistance	ASTM D 779 (minutes)	>60
Water Penetration Resistance	AATCC 127 (cm H ₂ O)	400
Air Resistance	ASTM E 2178 (L/s/m ² @ 75 Pa)	<.01
Flame Spread Index	ASTM E 84	Class A
Smoke Developed Index	ASTM E 84	Class A
Ultraviolet Light (UV) Exposure	Internal	180 Days

Test data is based on average results and is not limiting specifications. Normal manufacturing variation may produce results above or below typical data and should not be considered or interpreted as minimum or maximum values.

CCMC No. 13426-R Sheathing Membrane, Breather-Type
CCMC No. 13617-R Air Barrier



(800) 361-6503 • ca.drylinewrap.com

© 2021 Goodfellow, Inc. All rights reserved. DRYline® is a registered trademark of National Shelter Products, Inc. BROADCAST® and WRAPLAB® are registered trademarks of Jumpstart Consultants, Inc. DRYLINE HP_ENGLISH / 07-2021



BROADCAST® CUSTOM PRINTED ADVERTISING

How businesses can build a big name for themselves.

With BROADCAST Custom Printed Advertising, it's easy to turn your building into a billboard. We'll put any logo or advertising message on any wrap. Builders, lenders, or any business can promote itself using multiple, vivid colors and a large surface area, with a small roll order minimum. See how it works by visiting our WRAPLAB® at dryline.customprintwrap.com.

