



All-purpose for  
all seasons



## An all-purpose building wrap for all seasons.

**DRYline® MP, a building wrap that withstands the toughest conditions.**

Manufactured from non-perforated fabrics, DRYline MP protects against vapor intrusion, even in hot and humid weather. So vapor escapes

even if it builds up inside. Plus, with our exclusive BROADCAST® Custom Printed Advertising, you can display any custom logo or advertising message on your DRYline wrap — which can be ordered in the industry's smallest quantities.

### What Makes Dryline MP Superior?

- **STRENGTH:** More durable than the competition, and endures tough jobsite conditions.
- **WATER-RESISTANT:** Compliant with all North American water-resistance standards for building wrap.
- **BREATHABLE:** Reduces the potential for condensation buildup.
- **TRANSLUCENT:** Makes it easy to quickly locate studs, openings, and corners.
- **UV RESISTANT:** With a higher UV exposure rating than other brands, it may be left exposed for up to 180 days.
- **ENERGY-EFFICIENT:** Recognized as an air barrier material for energy efficiency standards.
- **DURABLE:** A better option for demanding jobsite conditions.

## DryLINE - Exclusively distributed in Canada by Goodfellow



For over 120 years, Goodfellow has been an industry leader in the distribution of building materials. With coast-to-coast distribution centers, they can service all regions in Canada, which enables customer's expectations to be met and exceeded time and time again in terms of quality and delivery lead times.

### WARRANTY INFORMATION

A ten (10) year limited warranty applies to DRYline MP building wrap. To obtain a copy of this warranty, please visit [drylinewrap.com](http://drylinewrap.com). No other warranty, express or implied, is given, including any implied warranty of merchantability or of fitness for a particular purpose.

### PRECAUTIONS

**Warning:** Protect from high heat or other ignition sources during shipment, storage and application.

### STORAGE

Protect DRYline building wrap from exposure to direct sunlight during storage. We recommend storage inside or under cover.

### ROLL SIZES\*

3' x 150'      9' x 100'      9' x 150'      9'6" x 95'  
10' x 90'      10' x 100'      10' x 150'

Other roll sizes available

\* Not all rolls available for BROADCAST Custom Printed Advertising, ask your sales representative for more details.

PROPERTY	STANDARD	TYPICAL RESULT
Tensile Strength (MD/CD)	ASTM D 5034 (lbs/inch)	50/45
Basis Weight	ASTM D 5261 (gsm)	80
Water Vapor Transmission Rate	ASTM E 96, Method A (grams/m <sup>2</sup> /24 hours)	126
Water Vapor Permeance	ASTM E 96, Method A (perms)	18
Water Resistance	ASTM D 779 (minutes)	>60
Water Penetration Resistance	AATCC 127 (cm H <sub>2</sub> O)	300
Air Resistance	ASTM E 2178 (L/s/m <sup>2</sup> @ 75 Pa)	0.01
Flame Spread Index	ASTM E 84	Class A
Smoke Developed Index	ASTM E 84	Class A
Ultraviolet Light (UV) Exposure	Internal	180 Days

*Test data is based on average results and is not limiting specifications. Normal manufacturing variation may produce results above or below typical data and should not be considered or interpreted as minimum or maximum values.*

CCMC Pending

**GOODFELLOW** 

(800) 361-6503 • [ca.drylinewrap.com](http://ca.drylinewrap.com)

© 2021 Goodfellow, Inc. All rights reserved. DRYline® is a registered trademark of National Shelter Products, Inc. BROADCAST® and WRAPLAB® are registered trademarks of Jumpstart Consultants, Inc. DRYLINE MP\_ENGLISH / 07-2021



### BROADCAST® CUSTOM PRINTED ADVERTISING

**How businesses can build a big name for themselves.**

With BROADCAST Custom Printed Advertising, it's easy to turn your building into a billboard. We'll put any logo or advertising message on any wrap. Builders, lenders, or any business can promote itself using multiple, vivid colors and a large surface area, with a small roll order minimum. See how it works by visiting our WRAPLAB® at [dryline.customprintwrap.com](http://dryline.customprintwrap.com).

