



GOODFELLOW *Terra*®

Sealer for Cuts in Pressure Treated Wood

Goodfellow Terra® Sealer is a colour-matched brush-on sealer and moisture repellent for cuts and holes in pressure treated wood that expose untreated wood, making it more vulnerable to rot and decay.

- For use **above ground** on deck boards, railing, post tops and fence boards
- Colour closely matches Goodfellow Terra Treated Wood
- Water-based formulation is low VOC and low odour
- Ready to use, directly from the can
- Soap and water clean-up / no special disposal requirements



**Sealed
Wood**

**Exposed
Wood**



Uses

For use on Above Ground treated wood products. Use Goodfellow Terra Sealer on areas that have been drilled or saw cut in treated wood deck boards, railing, post tops, fence boards, etc.

A 946 ml can will seal approx. 330 5/4x6 deck board ends or approx. 220 2x6 deck board ends, coated twice.

Goodfellow Terra® Sealer is not recommended to replace pressure treatment.

Do not use for pressure treated wood in ground contact applications or in preserved wood foundations.

Application

- Pressure treated wood should be dry and clean.
- Goodfellow Terra Sealer is ready to use – do not dilute.
- Shake or stir contents before and during use.
- Apply two coats by brush.
- Clean equipment (brushes, etc.) with soap and water.
- Store in tightly closed original container.
Do not freeze. Keep above 4° C (40° F).
- Dispose of empty container in household trash.